

Enabling Technology		All Comments						
Lasers	VCSELS: 2 mW preferably 10 mW, 795 and 780 nm, near shot noised limited performance. DFB lasers that cost \$1000. Lasers for pulsed optical pumping: 500 mW at 795 or 770 nm, linewidth; 1 GHz, repeatable power and wavelength.	The lack of VCSELS in the UK, and the struggles in mass-producing them, is proving to become problematic for OPM development.	prefer to have multi VCSEL sources. 1k/year now, potentially 100k/year in 5 years.	the laser frequency typically fluctuates by 50 MHz in a day	mWs, single mode	low-nose	high power vcsel	More compact high powered lasers
Optics/electro optical components	Extreme miniaturization for shuttering, amplitude control, and frequency modulation.	intergrated photonic systems, e.g. laser and cells	low-magnetization and high-bandwidth	miniaturized				
Vapor cell designs	Optical coating on the interior surfaces, both AR and HR. Operable up to 200 C for potassium. Sizes ranging from 1 mm <sup>3</sup> to 50 cm <sup>3</sup> . Ensure long lifetime of the alkali metal at high temperature.	Vapor cells are the decisive component for the performance of an OPM. Miniaturization is important	increase the number of atom and decrease the size of the cell	intra-cell optical elements and coatings	cell is the most important component	more compact	miniturize d	
Vapor cell packaging	Better thermal insulation. Maintain cell at 150 C for less than 500 mW of power.	High temperature paraffin coating	every bit of reduction in standoff helps	alkali+buffer gas cells with vacuum package	spin protecting cell coating	without glue	variable volume	Labs without cell fabrication could enter the field
Signal processing methods for specific applications	inverse problem							
Magnetic field stabilization and control technologies	For applications off the shelf products would lower development time	Larger dynamic range and mitigation of CAPE	high-stabilization current source	active noise compensation				
Scalable OPM array control technologies	>100 sensors	considering the cross-talks	Flexible standard electronics would lower costs					
Other	New Sensor Architectures - Dead Zone Free Operation, Low Heading Error, Higher Bandwidth/Dynamic Range etc.	detect high frequency brain signals (70-8,000 Hz)	Improving OPM dynamic range & noise	more attention to long-term stability	turnkey multi-opm-systems			